

MATERIAL SAFETY DATA SHEET

REVISION DATE: 03-03-2000

SUPERSEDES: 01-23-2000

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMPANY INFORMATION

Foster Products Corporation
H.B. Fuller Company Subsidiary
2900 Granada Lane
Oakdale, MN 55128
Phone: 651-236-3700

Medical Emergency Phone Number (24 Hours): 1-888-853-1758
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

PRODUCT INFORMATION

PRODUCT IDENTIFIER: 802297PM
PRODUCT NUMBER: FD3500
PRODUCT NAME: FOSTER 35-00
REGISTERED TRADE NAME: SEALFAS G-P-M MASTIC WHITE (TROWEL)
PRODUCT DESCRIPTION: Mastic

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for any additional exposure limit guidelines.

Chemical Name	CAS #	PERCENT	OSHA PEL
Aluminum oxide	1344-28-1	10 - 30	TWA (as Al) (Total dust) 10 MG/M3 TWA (as Al) (Respirable dust) 5 MG/M3
Calcium carbonate	1317-65-3	10 - 30	TWA (Total dust) 15 MG/M3 TWA (Respirable dust) 5 MG/M3
Titanium dioxide	13463-67-7	1 - 5	TWA (Total dust) 10 MG/M3
Vinyl acetate	108-05-4	0.1 - 1	TWA 10 ppm STEL 20 ppm

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS RATING: HEALTH -- 1 FLAMMABILITY -- 0 REACTIVITY -- 0

MATERIAL SAFETY DATA SHEET

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

EYE: Can cause minor irritation, tearing and reddening.

SKIN: Can cause minor skin irritation, defatting, and dermatitis.

INHALATION: Can cause minor respiratory irritation. Other possible symptoms include coughing or wheezing. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

INGESTION: Ingestion is not an anticipated route of exposure.

LONG-TERM (CHRONIC) HEALTH EFFECTS

TARGET ORGAN(S): Lungs

REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

Vinyl acetate

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Lung disease

SECTION 4: FIRST AID MEASURES

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF VAPORS INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT:	Non flammable
AUTOIGNITION TEMPERATURE:	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
UPPER EXPLOSIVE LIMIT (% in air):	Not established
EXTINGUISHING MEDIA:	Use water spray, foam, dry chemical or carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	There is a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers.
SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide, Carbon monoxide, Aluminum oxide

MATERIAL SAFETY DATA SHEET

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: No health effects expected from the cleanup of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this MSDS.

CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: Mildly irritating material. Avoid unnecessary exposure.

Storage: Store in a cool, dry place.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Wear safety glasses when handling this product.

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves.

GLOVES: Nitrile

RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

VENTILATION:

EXPOSURE LIMITS:

Chemical Name	ACGIH EXPOSURE LIMITS	AIHA WEEL
Aluminum oxide	TWA (Total dust) 10 MG/M3	Not established
Calcium carbonate	TWA (Total dust) 10 MG/M3	Not established
Titanium dioxide	TWA (Total dust) 10 MG/M3	Not established
Vinyl acetate	TWA 10 ppm STEL 15 ppm	Not established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

COLOR: White

MATERIAL SAFETY DATA SHEET

ODOR: Mild Sweet
ODOR THRESHOLD: Not established
WEIGHT PER GALLON (lbs.): 11.6
SPECIFIC GRAVITY: 1.39
SOLIDS (% by weight): 75.0

pH: 9.0
BOILING POINT (deg. C): Not established
FREEZING/MELTING POINT (deg. C): Not established
VAPOR PRESSURE (mm Hg): Not established
VAPOR DENSITY: Not established
EVAPORATION RATE: Not established
OCTANOL/WATER COEFFICIENT: Not established

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.
CHEMICAL INCOMPATIBILITY: Not established
HAZARDOUS POLYMERIZATION: Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, Aluminum oxide

SECTION 11: TOXICOLOGICAL INFORMATION

CHEMICAL NAME	LD50/LC50
Aluminum oxide	Not established
Calcium carbonate	Not established
Titanium dioxide	Not established
Vinyl acetate	Oral LD50 Rat = 2920 mg/kg Inhalation LC50 Rat = 11400 ml/cu m Dermal LD50 Rabbit = 2335 mg/kg

TOXICOLOGY SUMMARY: No additional health information available.

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available

SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information.

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

MATERIAL SAFETY DATA SHEET

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.

If you need more information about the inventory status of this product call 651-236-5858.

TSCA Section 12(b) - Export Notice Requirements

This product contains a chemical substance that is currently on the EPA's Section 12(b) Export List. Contact the company Global Regulatory Group at 651/236-5858 for the identity of the Section 12(b) chemical(s).

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 72. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
Aluminum oxide	1344-28-1	10 - 30
Vinyl acetate	108-05-4	0.1 - 1

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2B D2A

STATE REPORTING

This MSDS is not prepared for distribution in California.

SECTION 16: ADDITIONAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Foster Products Corporation from its suppliers, and because Foster Products Corporation has no control over the conditions of handling and use, Foster Products Corporation makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Foster Products Corporation assumes no responsibility for use or reliance thereon. It is the responsibility of the user of Foster Products Corporation products to comply with all applicable federal, state and local laws and regulations.