

## MATERIAL SAFETY DATA SHEET

REVISION DATE: 06-06-2001

SUPERSEDES: 07-06-2000

### SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### COMPANY INFORMATION

Foster Products Corporation  
H.B. Fuller Company Subsidiary  
2900 Granada Lane  
Oakdale, MN 55128  
Phone: 651-236-3700

Medical Emergency Phone Number (24 Hours): 1-888-853-1758  
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

#### PRODUCT INFORMATION

PRODUCT IDENTIFIER: 802420PM  
PRODUCT NUMBER: FD8560  
PRODUCT NAME: FOSTER 85-60  
REGISTERED TRADE NAME: QUICK-TACK ADHESIVE  
TRADEMARK: QUICK-TACK ADHESIVE™  
PRODUCT DESCRIPTION: Adhesive

### SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for any additional exposure limit guidelines.

Chemical Name	CAS #	PERCENT	OSHA PEL
Kaolin clay	1332-58-7	10 - 30	TWA (Total dust) 10 MG/M3 TWA (Respirable dust) 5 MG/M3
Oil, petroleum		10 - 30	TWA * Mist 5 MG/M3
Chlorinated paraffin	63449-39-8	1 - 5	Not established
Crystalline silica	14808-60-7	0.1 - 1	TWA (Respirable dust) 0.1 MG/M3

\*These exposure limits are for mineral oil mist, a related material.

### SECTION 3: HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

Cancer hazard.

HMIS RATING: HEALTH -- 1 FLAMMABILITY -- 0 REACTIVITY -- 0

## MATERIAL SAFETY DATA SHEET

---

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

### POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

EYE: No irritation hazard in normal industrial use.

SKIN: Can cause minor skin irritation, defatting, and dermatitis.

INHALATION: Can cause minor respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Overexposure to crystalline silica may cause silicosis.

INGESTION: Ingestion is not an anticipated route of exposure.

### LONG-TERM (CHRONIC) HEALTH EFFECTS

TARGET ORGAN(S): Lungs

### REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

Crystalline silica

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Lung disease

## **SECTION 4: FIRST AID MEASURES**

---

IF IN EYES: None expected to be needed, however, use an eye wash to remove a chemical from your eye regardless of the level of hazard.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF VAPORS INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

## **SECTION 5: FIRE FIGHTING MEASURES**

---

FLASH POINT:	Non flammable
AUTOIGNITION TEMPERATURE:	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
UPPER EXPLOSIVE LIMIT (% in air):	Not established
EXTINGUISHING MEDIA:	Use water spray, foam, dry chemical or carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	There is a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers.
SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide, Carbon monoxide, Chlorine containing gases, Nitrogen containing gases

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

---

SPECIAL PROTECTION: No health effects expected from the cleanup of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this MSDS.

CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to containers

## MATERIAL SAFETY DATA SHEET

for disposal. Keep spilled product out of sewers, watersheds, or water systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

### SECTION 7: HANDLING AND STORAGE

Handling: Mildly irritating material. Avoid unnecessary exposure.

This product contains an ingredient that may release formaldehyde at heated cure temperatures.

Storage: Store in a cool, dry place.

Consult the Technical Data Sheet for specific storage instructions.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Wear safety glasses when handling this product.  
SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves.  
GLOVES: Nitrile  
RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).  
VENTILATION: Use local exhaust ventilation or other engineering controls to minimize exposures.

#### EXPOSURE LIMITS:

Chemical Name	ACGIH EXPOSURE LIMITS	AIHA WEEL
Kaolin clay	TWA (Respirable dust) 2 MG/M3	Not established
Oil, petroleum	TWA * Mist 5 MG/M3	Not established
Chlorinated paraffin	Not established	Not established
Crystalline silica	TWA (Respirable dust) 0.05 MG/M3	Not established

\*These exposure limits are for mineral oil mist, a related material.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid  
COLOR: Beige  
ODOR: Mild Oily  
ODOR THRESHOLD: Not established  
WEIGHT PER GALLON (lbs.): 9.7  
SPECIFIC GRAVITY: 1.2

## MATERIAL SAFETY DATA SHEET

SOLIDS (% by weight): 60.5

pH: Not established

BOILING POINT (deg. C): Not established

FREEZING/MELTING POINT (deg. C): Not established

VAPOR PRESSURE (mm Hg): Not established

VAPOR DENSITY: Not established

EVAPORATION RATE: Not established

OCTANOL/WATER COEFFICIENT: Not established

### SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

CHEMICAL INCOMPATIBILITY: Not established

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, Chlorine containing gases, Nitrogen containing gases

### SECTION 11: TOXICOLOGICAL INFORMATION

CHEMICAL NAME	LD50/LC50
Kaolin clay	Not established
Oil, petroleum	Not established
Chlorinated paraffin	Oral LD50 Rat >21500 ml/kg Dermal LD50 Rabbit > 10 ml/kg
Crystalline silica	Not established

TOXICOLOGY SUMMARY: No additional health information available.

### SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available

### SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

### SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information.

### SECTION 15: REGULATORY INFORMATION

#### INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.

CANADIAN CEPA DSL: This product is in compliance with the Canadian Domestic Substance List requirements.

If you need more information about the inventory status of this product call 651-236-5858.

## MATERIAL SAFETY DATA SHEET

---

### TSCA Section 12(b) - Export Notice Requirements

This product contains a chemical substance that is currently on the EPA's Section 12(b) Export List. Contact the company Global Regulatory Group at 651/236-5858 for the identity of the Section 12(b) chemical(s).

### FEDERAL REPORTING

#### EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 72. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
Polychlorinated alkanes	63449-39-8	1 - 5

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2A

### STATE REPORTING

This MSDS is not prepared for distribution in California.

### **SECTION 16: ADDITIONAL INFORMATION**

---

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Foster Products Corporation from its suppliers, and because Foster Products Corporation has no control over the conditions of handling and use, Foster Products Corporation makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Foster Products Corporation assumes no responsibility for use or reliance thereon. It is the responsibility of the user of Foster Products Corporation products to comply with all applicable federal, state and local laws and regulations.