

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 05.10.2009

Revision: 05.10.2009

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** FOSTER 60-39
- **Application of the substance / the preparation** Masking material
- **Manufacturer/Supplier:**
Temati B.V.
Rijnland 2
NL-1948 RL Beverwijk
Tel: +31 251 229 172
Fax: +31 251 212 380
E-mail: temati@temati.com
- **Further information obtainable from:** Product safety department.
- **Information in case of emergency:** Tel: +31 251 229 172 (mo-fr/9-17)

2 Hazards identification

- **Hazard description:**



Xi Irritant
N Dangerous for the environment

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Has a narcotizing effect.

R 10 Flammable.

R 37 Irritating to respiratory system.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

Contains epoxy constituents. See information supplied by the manufacturer.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Xn, Xi, N; R 10-37-51/53-65-66-67	25-<50%
CAS: 1330-20-7 EINECS: 215-535-7	Xylene, mixed isomers, pure Xn, Xi; R 10-20/21-38	5-<10%
CAS: 2807-30-9 EINECS: 220-548-6	2-(propyloxy)ethanol Xn, Xi; R 21-36	1-<5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 05.10.2009

Revision: 05.10.2009

Trade name: FOSTER 60-39

(Contd. of page 1)

- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
 - Water
 - Water with full jet
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
 - Ensure good ventilation/exhaustion at the workplace.
 - Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

* 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 Xylene, mixed isomers, pure (5-<10%)

WEL ()	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV

- **CAS No. Designation of material % Type Value Unit**
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 05.10.2009

Revision: 05.10.2009

Trade name: FOSTER 60-39

(Contd. of page 2)

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

> 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

Goggles recommended during refilling

· Body protection: Use protective suit.

9 Physical and chemical properties

· General Information

Form:	Fluid
Colour:	Grey
Odour:	Characteristic

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 135°C

· Flash point: 24°C (DIN 53213)

· Ignition temperature: 450°C

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:	0.8 Vol %
Upper:	7.0 Vol %

· Vapour pressure At 20°C: 2 hPa

· Vapour pressure At 50°C: 13 hPa

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 05.10.2009

Revision: 05.10.2009

Trade name: FOSTER 60-39

(Contd. of page 3)

· Density At 20°C:	1.08 g/cm ³ (DIN 51757)
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· pH-value At 20°C:	7
· Viscosity: Dynamic At 20°C:	65000 mPas
· Solvent content: Organic solvents: Water:	55.0 % 0.2 %
· Solids content:	44.6 % (DIN 53216)
· Additional information: VOC (EU): VOC (EU):	54.96 % 593.6 g/l

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (RAT)
Dermal	LD50	>3400 mg/kg (RAT)
Inhalative	LC50/4 h	>10.2 mg/l (RAT)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

GB

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 05.10.2009

Revision: 05.10.2009

Trade name: FOSTER 60-39

(Contd. of page 4)

13 Disposal considerations

- **Product:**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11	waste paint and varnish containing organic solvents or other dangerous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 Flammable liquids.
- **Danger code (Kemler):** 30
- **UN-Number:** 1139
- **Packaging group:** III
- **Hazard label:** 3
- **Special marking:** Symbol (fish and tree)
- **Description of goods:** 1139 COATING SOLUTION, special provision 640E
- **Limited quantities (LQ) LQ7**
- **Transport category** 3
- **Tunnel restriction code** D/E

- **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1139
- **Label** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E
- **Marine pollutant:** Yes
Symbol (fish and tree)
- **Proper shipping name:** COATING SOLUTION

- **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1139
- **Label:** 3

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 05.10.2009

Revision: 05.10.2009

Trade name: FOSTER 60-39

(Contd. of page 5)

- **Packaging group:** III
- **Proper shipping name:** COATING SOLUTION

- **Transport/Additional information:**

For ADR and IMDG: Transport and packing are in accordance with the regulation for limited quantities. These products are therefore classified as no dangerous goods.

15 Regulatory information

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

The product has been marked in accordance with EU Directives / respective national laws.

The R and S phrases may be omitted if packaging contains no more than 0.125 litre.

- **Code letter and hazard designation of product:**



Xi Irritant

N Dangerous for the environment

- **Risk phrases:**

10 Flammable.

37 Irritating to respiratory system.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

- **Safety phrases:**

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

24/25 Avoid contact with skin and eyes.

43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.

57 Use appropriate container to avoid environmental contamination.

60 This material and its container must be disposed of as hazardous waste.

- **Special labelling of certain preparations:**

Contains epoxy constituents. See information supplied by the manufacturer.

- **National regulations:**

- **Technical instructions (air):**

Class	Share in %
Water	0.2
III	0.3
NK	55.0

- **Waterhazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases:**

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

21 Harmful in contact with skin.

36 Irritating to eyes.

37 Irritating to respiratory system.

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 05.10.2009

Revision: 05.10.2009

Trade name: FOSTER 60-39

(Contd. of page 6)

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Product safety department.

· **Contact:** temati@temati.com

· *** Data compared to the previous version altered.**

GB