



## Fire resistant coating



- **Excellent protection from the effects of fire**
- **Quick and easy to apply**
- **Provides semi-permeable, durable finish**
- **Tested to EN 1366-3**



## Description

A high quality, white acrylic emulsion coating. The coating has 240 minutes proven fire resistance when tested to EN 1366-3: 2004. This coating is designed for applications in the installation of pre-coated and plain mineral fibre batts, as well as coating cables and pipes, in large service openings in compartment walls and floors. The coating is quick and easy to apply using brush, spray or knife. The coating dries quickly to form a semi-permeable and durable finish that is washable and resistant to mould and insect attack.

## Characteristics

Colour :	White
Form :	Thixotropic Liquid
Weight per litre :	1,36 kg (55% solids)
Composition :	Acrylic co-polymer emulsion
Packaging :	5 litre buckets
Shelf life :	At least 6 months from date of delivery, when stored unopened in a cool, dry place, within the temperature range (+5°C to +25°C) and out of direct sunlight. Protect from frost
Drying time :	Touch: 30 - 120 minutes Thorough : 6 - 8 hours
Service temperature :	-20°C to +90°C
Application temperature :	Above + 5°C
Fire behaviour :	up to 240 minutes proven fire resistance using the principles of EN 1366-3: 2004
Coverage :	2.6 - 5.1 m <sup>2</sup> per litre per coat (dependant on substrate)